MOTOR DATA @ 230 VAC (TRAP)

MOTOR PARAMETERS		UNITS	VALUE
HORSEPOWER	HP RATED	Hp	1.2
KILOWATTS	KW RATED	KW	.88
MAX. OPERATING SPEED	N MAX	RPM	2100
SPEED @ RATED TORQUE	N RATED	RPM	1500
* CONTINUOUS RATED TORQUE @ 1500 RPM		IN-LBS[Nm]	50.0[5.6]
* CONTINUOUS STALL TORQUE		IN-LBS[Nm]	54.0[6.1]
CONTINUOUS LINE CURRENT		AMPS	4.4
PEAK TORQUE	Tpk	IN-LBS[Nm]	189.0[21.3]
PEAK CURRENT		AMPS	15.3
MAX. THEORETICAL ACCEL.		RAD/SEC²	54,000
TORQUE SENSITIVITY	Kt	IN-LBS/AMP[Nm/AMP]	12.4[1.40]
BACK EMF (LINE TO LINE)	±10%	Vrms/Krpm	110.0
D.C. RESISTANCE (P-P)	±10%	OHMS	3.3
INDUCTANCE (P-P)	±10%	MILLIHENRIES	24.4
ROTOR INERTIA W/BRAKE	Jm	IN-LBS-SEC²[Kg-M²]	.0039[.00044]
STATIC FRICTION	Tf	IN-LBS[Nm]	1.0[0.11]

*25°C AMBIENT WITH A MAXIMUM CASE TEMPERATURE OF 100°C ON MOTOR. MOTOR MOUNTED ON A 12" X 12" X 1/2" ALUMINUM HEATSINK. THERMOSTAT IN STATOR WINDINGS WILL OPEN IF WINDING TEMPERATURE EXCEEDS 155°C. THIS ALLOWS FOR AN APPROXIMATE +10% HEADROOM IN THE CONTINUOUS TORQUE RATING BEFORE THERMOSTAT OPENS.

MECHANICAL NOTES:
1. AXIAL LOAD: 50 LBS MAX
2. RADIAL LOAD: 100 LBS MAX @ 1" FROM FACE
3. MOTOR SEALED TO IP65.
4. MOTOR WEIGHT: 24.3 LBS. [11.0 Kg]
5. MOTOR FINISH: BLACK EPOXY
6. MOTOR OUTPUT SHAFT: STAINLESS STEEL
7. INCHES (MILLIMETERS)

FAILSAFE BRAKE: (290-00006)
MIN. HOLDING TORQUE: 240 IN-LBS
INPUT VOLTAGE: 24 VOLTS

CONNECTION CHART

MOTOR WIRE LEADS		
TERMINAL	WIRE FUNCTION	WIRE COLOR
–	ΦR	RED
–	ΦS	BLACK
–	ΦT	BLUE
–	PE GND	GRN/YEL

RES/THERM/BRK WIRE LEADS		
TERMINAL	WIRE FUNCTION	WIRE COLOR
S11	BRK (+)	BLUE
S10	BRK (–)	BLUE
S9	REF GND	YEL/WHT
S8	REF	RED/WHT
S7	SIN	YELLOW
S6	COS	RED
S5	COS GND	BLACK
S4	SIN GND	BLUE
S3	THERM	BLACK
S2	THERM	BLACK
S1	RES SHLD	GRN/YEL





SCHEMATIC DRAWING FOR BRUSHLESS RESOLVER





REVISIONS			
REV.	DESCRIPTION	DATE	APPD.
	PRELIMINARY	7/14/00	LIN

TITLE: "B"/230/MET/RES/NPT/BRK
DRAWING NUMBER: MPM1141BTG7G3R

NO.	PART NUMBER	DESCRIPTION	QTY.

TOLERANCES UNLESS SPECIFIED
DECIMAL .XXX ± .005
DECIMAL .XX ± .010
DECIMAL .X ± .020
FRACTION ± 1/64
ANGLE ± 1/2°

MTS Systems Corporation
Automation Division

PROPRIETARY RIGHTS OF MTS AUTOMATION ARE INCLUDED IN THE INFORMATION DISCLOSED HEREIN. THIS DRAWING AND/OR DOCUMENT SHALL NOT BE REPRODUCED OR TRANSFERRED TO OTHER DOCUMENTS OR USED OR DISCLOSED TO OTHERS FOR ANY PURPOSE EXCEPT FOR WHICH WAS SPECIFICALLY FURNISHED.

DRAWN: LIN
DATE: 7/14/00
CHECKED:
APPROVED:
TITLE: "B"/TRP/230/MET/RES/NPT/BRK
REV.
MATERIAL:
DRAWING NUMBER: MPM1141BTG7G3R
SCALE: 1/2:1